



HIKVISION
intrusion

Wired volumetric triple technology detector

XDH10TT-AM

DETECTION

Detector type	Wired
Installation height	2.4 m
Angle detection	90°
Detection distance	10 m
Detection method	Infrared and microwave
Detection speed	0.25 m/s - 3 m/s
Detection zones	78 (24 with curtain lens)
Pets immunity	Up to 10 kg
Antimasking	Yes
Adjustable antimasking	Sí
Detection technology	Volumetric triple technology

TECHNICAL SPECIFICATIONS

LED indicators	Yes
Tamper	Yes
EOL resistors (end of line)	Sí
Test buzzer	Sí

AMBIENT

Operating temperature	-30 °C ~ 40 °C
Degree of protection	IP55
Use	Indoor-outdoor

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	IV

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Alarm Consumption	30mA
Standby consumption	23mA

SENSOR

Type of sensor	PIR and microwave
Double PIR sensor	Sí
Microwave	9.87 GHz / 9.90 GHz / 9.91 GHz
Digital temperature compensation	Yes

MATERIAL AND DIMENSIONS

Installation	Wall
Dimensions	118 x 77 x 84 mm
Net weight	300 g

