



HIKVISION
accessories

Access control indoor with keyboard / card mifare 13.56mhz

DS-K1T802M

FUNCTIONS

General	Sí
Patrol	Sí
Blacklist	Sí
Duress	Sí
Open door alarm	Sí
Memoria insuficiente	Sí
Alarma desconectada	Sí
Puerta Forzada	Sí

FEATURES

Screen	Yes
Type of screen	STN de matriz de puntos de 128 x 64
Integrated controller	Sí
LED indicator	Yes
Sound warning	Yes
Watchdog design	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	170mA

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	32 bits
Software	iVMS-4200 / Hik-Connect / iVMS-5200
Software included	Sí

MATERIAL AND DIMENSIONS

Dimensions	126.5 x 94.5 x 24 mm
------------	-----------------------------

IDENTIFICATION

Mode	Keyboard / Card
Keyboard	Yes
Type of card	MIFARE 13.56MHz
Number of cards	3000
Number of register	10000

INPUTS/OUTPUTS

Door sensor	1
Exit button	1
Blocking output	1
Bell	Sí

AMBIENT

Operating temperature	-20 °C ~ 65 °C
Use	Indoor
Maximum humidity	90%

GENERAL INFORMATION

Serie	HikA-P
Control type	Access control

COMMUNICATION

TCP/IP	Sí
--------	-----------

