

HIKVISION
HiWatch Series



Bullet ip camera of 4 megapixels and fix lens

HWI-B140H-M

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 3Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 / 320 × 240 (25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	100°

AMBIENT

Operating temperature	-30 °C ~ 50 °C
Degree of protection	IP67

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S y G
Maximum number of users	Up to 32 users
Web browser	Explorer / Chrome / Firefox / Safari
Management software	iVMS-4200 / iVMS-5200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/1.3'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.1Lux

DISTANCE DORI

Detect	56 m
Observe	23 m
Recognize	11 m
Identify	5 m

MATERIAL AND DIMENSIONS

Dimensions	191.3 x 70 (Ø) mm
Material	Metal
Net weight	400 g
Weight with packaging	640 g

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
Motion detection	Yes
Video Tamper	Si

AXES

Motion	3-Axis
--------	---------------

technical datasheet

Use	Indoor-outdoor
Maximum humidity	95%

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Wavelength	850 nm

GENERAL INFORMATION

Technology	IP
Type of camera	Bullet

STORAGE

Storage Systems

NAS

