



**HIKVISION**  
accessories

## Ip of surface / embed video intercom

**DS-KV8413-WME1(B)**

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>10W</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

### AMBIENT

Operating temperature	<b>-40 °C ~ 55 °C</b>
Degree of protection	<b>IP65</b>
Anti vandal	<b>IK08</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	<b>TCP / IP</b>
Memory slot	<b>SD up to 128Gb</b>
IP connection	<b>10M/100Mbps</b>
Wi-Fi	<b>Sí</b>
Tipo de Wi-Fi	<b>2.4 GHz</b>

### AUDIO (VIDEO INTERCOM)

Sound input	<b>Multidirectional microphone</b>
Sound output	<b>Built-in speaker</b>
Bidirectional audio	<b>Sí</b>
Audio compression	<b>G.711</b>

### INPUTS/OUTPUTS

Alarm input	<b>4</b>
RS485	<b>1</b>
Relay NO/NC	<b>2</b>

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	<b>Sí</b>
--------	-----------

### CAMERA

Resolution	<b>2 Mpx</b>
Horizontal viewing angle	<b>129°</b>
Diagonal angle of view	<b>75°</b>
Night vision	<b>Sí</b>
Video compression	<b>H.264</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Surface / embed</b>
Dimensions	<b>174 x 91 x 29 mm</b>
Net weight	<b>380 g</b>
Weight with packaging	<b>590 g</b>

### SPECS AND FEATURES

Serie	<b>PVPH</b>
Technology	<b>IP</b>
Number of homes	<b>4</b>

### OPENING

Call elements	<b>4 Botones sencillos</b>
Proximity reader	<b>MIFARE cards</b>

### SYSTEM (RECORDERS)

Operating system	<b>Embedded LINUX</b>
------------------	-----------------------

