

HIKVISION
HiWatch Series



Ip recorder of 16 channel and 8 mpx resolution with 16 PoE ports

HWN-5216MH-16P

NETWORK FEATURES

PoE ports	16
Number of ports RJ45	1
Speed RJ45	10 / 100 / 1000 Mbps
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Type PoE	802.3at / af
PoE consumption	200W
Software	IVMS
App	Hik-Connect

RECORDING

Maximum recording resolution	8 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Channels that support the maximum recording resolution	4K solo en 2 canales
Resolutions	4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
ANR (Redundant Recording in SD)	Sí
Output bandwidth	160Mbps

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	1
USB 3.0	1
Alarm output	1

GENERAL INFORMATION

Serie	HiWatch
Technology	IP
Compatibility	Hikvision HA series cameras

AUDIO

Audio Inputs	1
Audio Outputs	1

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W
Amperage	1000mA

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	3000 g

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
VGA resolution	1080P

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

VIDEO

IP Channels	16
-------------	-----------

technical datasheet

Audio bidirectional (Full-duplex) **Yes**

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle **Yes**

Motion detection **Yes, 2.0**

