



## Ip of surface video intercom VTO2211G-P

### CAMERA

|                          |               |
|--------------------------|---------------|
| Resolution               | <b>2 Mpx</b>  |
| Sensor                   | <b>CMOS</b>   |
| Sensor size              | <b>1/2.8"</b> |
| Horizontal viewing angle | <b>125°</b>   |
| Diagonal angle of view   | <b>142°</b>   |
| Night vision             | <b>Si</b>     |
| Day / Night              | <b>ICR</b>    |
| Video compression        | <b>H.264</b>  |

### POWER CONSUMPTION

|                     |                                 |
|---------------------|---------------------------------|
| Power mode          | <b>DC</b>                       |
| Voltage             | <b>12V</b>                      |
| Consumption (w)     | <b>7W</b>                       |
| Amperage            | <b>1000mA</b>                   |
| PoE power           | <b>Yes</b>                      |
| Standby consumption | <b>less than or equal to 1W</b> |

### AMBIENT

|                       |                                             |
|-----------------------|---------------------------------------------|
| Operating temperature | <b>-30 °C ~ 60 °C</b>                       |
| Degree of protection  | <b>IP65</b>                                 |
| Use                   | <b>Exterior (silicone sealant required)</b> |
| Maximum humidity      | <b>90%</b>                                  |

### MATERIAL AND DIMENSIONS

|              |                            |
|--------------|----------------------------|
| Installation | <b>Surface</b>             |
| Dimensions   | <b>150 x 100 x 24.8 mm</b> |

### OPENING

|                  |                      |
|------------------|----------------------|
| Call elements    | <b>Simple button</b> |
| Proximity reader | <b>MIFARE cards</b>  |

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

|        |           |
|--------|-----------|
| Tamper | <b>Si</b> |
|--------|-----------|

### INPUTS/OUTPUTS

|                 |          |
|-----------------|----------|
| Alarm input     | <b>1</b> |
| RS485           | <b>1</b> |
| Door sensor     | <b>2</b> |
| Exit button     | <b>1</b> |
| Blocking output | <b>1</b> |
| Alarm output    | <b>1</b> |

### AUDIO (VIDEO INTERCOM)

|                     |                               |
|---------------------|-------------------------------|
| Sound input         | <b>1</b>                      |
| Sound output        | <b>Built-in speaker</b>       |
| Bidirectional audio | <b>Si</b>                     |
| Audio compression   | <b>G.711MU / G.711U / PCM</b> |

### GENERAL INFORMATION

|                 |           |
|-----------------|-----------|
| Technology      | <b>IP</b> |
| Number of homes | <b>1</b>  |

### SYSTEM (RECORDERS)

|                  |                           |
|------------------|---------------------------|
| Processor        | <b>Embedded Processor</b> |
| Operating system | <b>Embedded LINUX</b>     |

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|               |                    |
|---------------|--------------------|
| IP connection | <b>10M/100Mbps</b> |
| ONVIF         | <b>Yes</b>         |

