



Ip of surface video intercom VTO2211G-WP

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.8"
Horizontal viewing angle	125°
Diagonal angle of view	142°
Night vision	Sí
Day / Night	ICR
Video compression	H.264

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af
Standby consumption	less than or equal to 1W
Consumption On	menor o igual a 7W

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / IPv4 / RTSP / RTP / TCP / UDP
IP connection	10M/100Mbps
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n
ONVIF	Yes

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711MU / G.711U / PCM

OPENING

Call elements	Simple button
Proximity reader	MIFARE cards

INPUTS/OUTPUTS

Alarm input	1
RS485	1
Door sensor	1
Botón de salida	1
Blocking entry	1
Alarm output	1

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Use	Exterior (silicone sealant required)
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	150 x 100 x 24.8 mm
Net weight	490 g
Weight with packaging	520 g

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

GENERAL INFORMATION

Technology	IP
------------	-----------

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------

