



Ip of surface video intercom

VTO3211D-P2-S2

technical datasheet

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.8"
Horizontal viewing angle	129°
Diagonal angle of view	147°
Night vision	SI
Day / Night	ICR
Video compression	H.264

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af
Standby consumption	less than or equal to 1W
Consumption On	menor o igual a 7W

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Exterior (silicone sealant required)
Maximum humidity	95%

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / DNS / RTSP / RTP / TCP / UDP
IP connection	10M/100Mbps
ONVIF	Yes

OPENING

Call elements	2 Botones sencillos
Proximity reader	Yes

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	SI
--------	----

INPUTS/OUTPUTS

Alarm input	1
RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	181 x 101 x 31 mm
Net weight	470 g
Weight with packaging	660 g

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	SI
Audio compression	G.711MU / G.711U / PCM

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

GENERAL INFORMATION

Technology	IP
------------	----

