



ZKTeco

Access control indoor-outdoor
with facial / palm of hand / card
rfid 125khz

GL-PROFACE-X-P-1-W

IDENTIFICATION

Mode	Facial / Palm of hand / Card
Type of card	RFID 125KHz
Number of cards	50000
Algorithm	ZKFace V12.0
NUmber of register	1000000
Number of faces	30000
Face recognition speed	0.3 s
Number of palms of hands	5000
Anti-counterfeiting	Yes
False positive ratio (FAR) palm	$\leq 0.01\%$
Negative false ratio (FRR) palm	$\leq 1\%$

AMBIENT

Operating temperature	-30 °C ~ 55 °C
Degree of protection	IP68
Anti vandal	IK04
Use	Indoor-outdoor
Maximum humidity	93%

FEATURES

Integrated controller	Sí
LCD screen	Yes, 8 touch"
Resolution LCD screen	1280 x 800
Camera	2 Mpx WDR Low Light

MATERIAL AND DIMENSIONS

Dimensions	227 x 143 x 26.1 mm
Net weight	990 g
Weight with packaging	2000 g

COMMUNICATION

TCP/IP	Sí
Mode	Wiegand / RS485 / RS232

FUNCTIONS

Duress	Sí
Grupos de vacaciones	Yes
Antipassback	Sí
Summertime programming (DST)	Sí
Tamper	Yes
Mask detection alarm	Yes

INPUTS/OUTPUTS

Door sensor	1
Botón de salida	1
Blocking output	1
Alarm output	1
Input devices	1 aux

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	2000mA

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Memory	512 MB RAM / 8192 MB Flash
Software	ZKBioSecurity
CPU	Dual-Core 900MHz

GENERAL INFORMATION

Control type	Access control
--------------	----------------

