



Milesight

Minidome ip camera of 5 megapixels and optical zoom lens

MS-C5375-FPC

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 28 areas
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
EIS	Yes
Main stream	5Mpx (1 ~ 25fps) / 3Mpx (1 ~ 45fps) / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 50fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 / 320 x 240 / 320 x 192 / 320 x 180 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 320 x 240 / 320 x 192 / 320 x 180 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
DISTANCE DORI	
Detect (Open lens)	57 m
Detect (Closed Lens)	283 m
Observe (Open lens)	22 m
Observe (Closed lens)	112 m
Recognize (Open lens)	11 m
Recognize (Closed lens)	56 m

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Face detection	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Sí
Heatmap	Yes
People counting	Yes
Loitering detection	Sí
Classification Human / vehicle	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2592 x 1944
Sensor Size	1/2.8'
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.005Lux
Ratio S / N	More than 55dB

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	90%

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes

technical datasheet

Identify (Open lens)	6 m
----------------------	-----

Identify (Closed lens)	28 m
------------------------	------

POWER CONSUMPTION

Power mode	DC
------------	----

Voltage	12V
---------	-----

Consumption (w)	9W
-----------------	----

Amperage	750mA
----------	-------

PoE power	Yes
-----------	-----

Type PoE	PoE 802.3af
----------	-------------

LENS

Lens Type	Optical zoom
-----------	--------------

Focal distance	2.7 mm ~ 13.5 mm
----------------	------------------

Maximum diaphragm opening	F/1.4
---------------------------	-------

Angle of View	99° ~ 31°
---------------	-----------

Autofocus	Yes
-----------	-----

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Audio compression	G.711 / G.722 / G.726 / AAC
-------------------	-----------------------------

Sampling frequency	8 kHz 16 kHz 32 kHz 44.1 kHz 48 kHz
--------------------	-------------------------------------

Bit rate	16 Kbps ~ 256 Kbps
----------	--------------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	NAS / Micro SD / Recorder
-----------------	---------------------------

ANR (Redundant Recording in SD)	Yes
---------------------------------	-----

AXES

Motion	3-Axis
--------	--------

Network disconnection	Yes
-----------------------	-----

NIGHT VISION

Night vision distance	50 m
-----------------------	------

Type of night vision	IR
----------------------	----

Smart IR	Yes
----------	-----

Starlight	Yes
-----------	-----

GENERAL INFORMATION

Serie	AI Mini Camera Series
-------	-----------------------

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

MATERIAL AND DIMENSIONS

Dimensions	115 x 130 (Ø) mm
------------	------------------

Net weight	780 g
------------	-------

