



**HIKVISION**  
HiWatch Series

Minidome 4 in 1 (cvi, tvi, ahd and analog) camera of 5 megapixels and fix lens

**HWT-T150-M**

## VIDEO (CAMERAS)

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Video Resolution  | <b>5 Megapixels</b>                                    |
| BLC               | <b>Yes</b>                                             |
| HLC               | <b>Yes</b>                                             |
| AGC               | <b>Yes</b>                                             |
| AWB               | <b>Yes</b>                                             |
| WDR               | <b>DWDR</b>                                            |
| Images per second | <b>20fps</b>                                           |
| Video output      | <b>1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS</b> |
| Day / night mode  | <b>Colour</b>                                          |
| Mirror            | <b>On / Off</b>                                        |

## POWER CONSUMPTION

|                 |              |
|-----------------|--------------|
| Power mode      | <b>DC</b>    |
| Voltage         | <b>12V</b>   |
| Consumption (w) | <b>4.3W</b>  |
| Amperage        | <b>360mA</b> |

## NIGHT VISION

|                       |             |
|-----------------------|-------------|
| Night vision distance | <b>20 m</b> |
| Type of night vision  | <b>IR</b>   |
| Smart IR              | <b>Yes</b>  |
| EXIR                  | <b>Yes</b>  |

## DISTANCE DORI

|           |             |
|-----------|-------------|
| Detect    | <b>69 m</b> |
| Observe   | <b>27 m</b> |
| Recognize | <b>14 m</b> |
| Identify  | <b>7 m</b>  |

## LENS

|                |               |
|----------------|---------------|
| Lens Type      | <b>Fix</b>    |
| Focal distance | <b>2.8 mm</b> |
| Angle of View  | <b>85°</b>    |

## IMAGE

|                          |                          |
|--------------------------|--------------------------|
| Sensor                   | <b>CMOS ®</b>            |
| Sensor resolution        | <b>2560 x 1944</b>       |
| Electronic shutter speed | <b>1/25s ~ 1/50,000s</b> |
| Minimum lighting         | <b>0.01Lux</b>           |

## AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP66</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

## MATERIAL AND DIMENSIONS

|                       |                            |
|-----------------------|----------------------------|
| Dimensions            | <b>82.6 x 91 x 69.7 mm</b> |
| Material              | <b>Metal</b>               |
| Net weight            | <b>230 g</b>               |
| Weight with packaging | <b>300 m</b>               |

## GENERAL INFORMATION

|                |                                          |
|----------------|------------------------------------------|
| Serie          | <b>HiWatch</b>                           |
| Technology     | <b>4 IN 1 (CVI, TVI, AHD and analog)</b> |
| Type of camera | <b>Minidome</b>                          |

## AXES

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

