



**Milesight**

Minidome ip camera of 5 megapixels and fix lens

MS-C5375-PD/J

## VIDEO (CAMERAS)

|                   |                                                                          |
|-------------------|--------------------------------------------------------------------------|
| Video Resolution  | 5 Megapixels                                                             |
| BLC               | Yes                                                                      |
| HLC               | Yes                                                                      |
| 3D-NR             | Yes                                                                      |
| AGC               | Yes                                                                      |
| AWB               | Yes                                                                      |
| WDR               | WDR (120 dB)                                                             |
| Images per second | 25fps                                                                    |
| Video output      | RJ45                                                                     |
| Day / night mode  | Automatic / Manual                                                       |
| Privacy mask      | Up to 4 zones                                                            |
| Anti fog system   | Yes                                                                      |
| Type of Codex     | CBR / VBR                                                                |
| Bit rate          | 16Kbps ~ 16Mbps                                                          |
| Compression       | H.265+ / H.265 / H.264                                                   |
| Main stream       | 5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)              |
| Sub stream        | 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)                |
| Sub stream 2      | 1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps) |
| Watermark         | Yes                                                                      |
| Anti flap         | Yes                                                                      |

## IMAGE

|                          |                  |
|--------------------------|------------------|
| Sensor                   | CMOS ®           |
| Sensor resolution        | 2592 x 1944      |
| Sensor Size              | 1/2.8"           |
| Electronic shutter speed | 1s to 1/100,000s |
| Minimum lighting         | 0.005Lux         |
| Ratio S / N              | More than 55dB   |

## LENS

|                |        |
|----------------|--------|
| Lens Type      | Fix    |
| Focal distance | 2.8 mm |

## VIDEO ANALYSIS

| Detection type                 | Analytical with human/vehicle classification in line/area crossing |
|--------------------------------|--------------------------------------------------------------------|
| Crossing line                  | Yes                                                                |
| Motion detection               | Yes                                                                |
| Abandoned object               | Yes                                                                |
| Missing object                 | Yes                                                                |
| Video Tamper                   | Yes                                                                |
| Loitering detection            | Yes                                                                |
| Classification Human / vehicle | Yes                                                                |

## AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40 °C ~ 60 °C |
| Degree of protection  | IP67           |
| Anti vandal           | IK10           |
| Use                   | Indoor-outdoor |
| Maximum humidity      | 90%            |

## NETWORK FEATURES

|                       |                         |
|-----------------------|-------------------------|
| IP connection         | 1 RJ45 (10M / 100M)     |
| ONVIF                 | Yes, type S, G, T and Q |
| Management software   | Milesight CMS           |
| IP address filter     | Yes                     |
| Network disconnection | Yes                     |

## DISTANCE DORI

|           |      |
|-----------|------|
| Detect    | 59 m |
| Observe   | 23 m |
| Recognize | 12 m |
| Identify  | 6 m  |

## GENERAL INFORMATION

|                |                       |
|----------------|-----------------------|
| Serie          | AI Mini Camera Series |
| Technology     | IP                    |
| Type of camera | Minidome              |

## NIGHT VISION

# technical datasheet

|                           |              |
|---------------------------|--------------|
| Maximum diaphragm opening | <b>F/1.6</b> |
| Angle of View             | <b>105°</b>  |

## AUDIO(CAMERAS)

|                     |                                         |
|---------------------|-----------------------------------------|
| Built in microphone | <b>Yes</b>                              |
| Audio compression   | <b>G.711 / G.722 / G.726 / AAC</b>      |
| Sampling frequency  | <b>8 kHz / 16 kHz / 32 kHz / 48 kHz</b> |
| Bit rate            | <b>16 Kbps ~ 256 Kbps</b>               |

## POWER CONSUMPTION

|                 |                    |
|-----------------|--------------------|
| Consumption (w) | <b>5.8W</b>        |
| PoE power       | <b>Yes</b>         |
| Type PoE        | <b>PoE 802.3af</b> |

## MATERIAL AND DIMENSIONS

|                       |                          |
|-----------------------|--------------------------|
| Dimensions            | <b>96.5 x 108 (Ø) mm</b> |
| Net weight            | <b>600 g</b>             |
| Weight with packaging | <b>730 g</b>             |

## AXES

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

|                       |             |
|-----------------------|-------------|
| Night vision distance | <b>25 m</b> |
| Type of night vision  | <b>IR</b>   |
| Starlight             | <b>Yes</b>  |

## STORAGE

|                                 |                                  |
|---------------------------------|----------------------------------|
| MicroSD-Card                    | <b>Up to 256Gb</b>               |
| Storage Systems                 | <b>NAS / Micro SD / Recorder</b> |
| ANR (Redundant Recording in SD) | <b>Yes</b>                       |

