



Milesight

Minidome ip camera of 5 megapixels and optical zoom lens

MS-C5375-FPC-B

VIDEO (CAMERAS)

Resolución vídeo	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 28 areas
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
EIS	Yes
Main stream	5Mpx (1 ~ 25fps) / 3Mpx (1 ~ 45fps) / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 50fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 / 320 x 240 / 320 x 192 / 320 x 180 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 320 x 240 / 320 x 192 / 320 x 180 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
DISTANCE DORI	
Detect (Open lens)	57 m
Detect (Closed Lens)	283 m
Observe (Open lens)	22 m
Observe (Closed lens)	112 m
Recognize (Open lens)	11 m
Recognize (Closed lens)	56 m

VIDEO ANALYSIS

Crossing line	Yes
Face detection	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Sí
Heatmap	Yes
People counting	Yes
Loitering detection	Sí
Classification Human / vehicle	Sí

IMAGE

Sensor	CMOS ®
Resolución sensor	2592 x 1944
Sensor Size	1/2.8'
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.005Lux
Ratio S / N	More than 55dB

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.4
Angle of View	99° ~ 31°
Autofocus	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

GENERAL INFORMATION

Serie	AI Mini Camera Series
Technology	IP

technical datasheet

Identify (Open lens)	6 m
----------------------	-----

Identify (Closed lens)	28 m
------------------------	------

AMBIENT

Operating temperature	-40 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Anti vandal	IK10
-------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	90%
------------------	-----

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Audio compression	G.711 / G.722 / G.726 / AAC
-------------------	-----------------------------

Sampling frequency	8 kHz 16 kHz 32 kHz 44.1 kHz 48 kHz
--------------------	-------------------------------------

Bit rate	16 Kbps ~ 256 Kbps
----------	--------------------

NIGHT VISION

Night vision distance	50 m
-----------------------	------

Smart IR	Yes
----------	-----

Starlight	Yes
-----------	-----

MATERIAL AND DIMENSIONS

Dimensions	115 x 130 (Ø) mm
------------	------------------

Net weight	780 g
------------	-------

Color	Black
-------	-------

AXES

Motion	3-Axis
--------	--------

Type of camera	Minidome
----------------	----------

POWER CONSUMPTION

Consumption (w)	9W
-----------------	----

PoE power	Yes
-----------	-----

Type PoE	PoE 802.3af
----------	-------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	NAS / Micro SD / Recorder
-----------------	---------------------------

ANR (Redundant Recording in SD)	Yes
---------------------------------	-----

