



Ip of surface video intercom VTO3311Q-WP

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.8"
Horizontal viewing angle	125°
Diagonal angle of view	139°
Night vision	Sí
Day / Night	Imagen en color
Video compression	H.265

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af
Standby consumption	3W
Consumption On	6W

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	90%

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	RTSP / DNS / P2P / UPnP / RTP / RTMP / SIP / SSH
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n
ONVIF	Yes

OPENING

Call elements	1 / 2 / 4 simple buttons
Proximity reader	Yes

SYSTEM (RECORDERS)

INPUTS/OUTPUTS

Alarm input	1
RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	188.1 x 107.2 x 30 mm
Material	Anodized aluminum
Net weight	55 g
Weight with packaging	820 g

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711A/G.711U/PCM

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Memory slot	SD up to 256Gb

GENERAL INFORMATION

Technology	IP
------------	-----------

Processor

Embedded Processor

