



HIKVISION
accessories

Access control indoor with keyboard / card mifare 13.56mhz

DS-K1T105AM

IDENTIFICATION

Mode	Keyboard / Card
Type of card	MIFARE 13.56MHz
Maximum reading distance	0 ~ 5 cm
Card reading time	menos de 1 s
Number of cards	100000
NUmber of register	300000
Multi-factor authentication	Yes

INPUTS/OUTPUTS

USB 2.0	1
RS485	1
Door sensor	1
Exit button	1
Blocking output	1
Speaker	1

FUNCTIONS

Duress alarm	Sí
Antipassback	Sí
Puerta Forzada	Sí
Tamper	Yes

MATERIAL AND DIMENSIONS

Dimensions	142 x 137 x 35 mm
Net weight	260 g
Weight with packaging	685 g

COMMUNICATION

TCP/IP	Sí
Wi-Fi	Sí

FEATURES

Integrated controller	Sí
Sound warning	Yes
Tamper	Sí
LCD screen	Sí, 2,8 Color"
Screen resolution	320 x 240
Watchdog design	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	2000mA

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Use	Indoor
Maximum humidity	90%

GENERAL INFORMATION

Serie	HikA-P
Control type	Access control

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	Linux
----------------	--------------

