



Minidome hd-cvi camera of 5 megapixels and optical zoom lens

HAC-HDBW1500R-Z-S2

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
2D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS
Day / night mode	Automatic
OSD menu	Yes
Privacy mask	Up to 8 zones
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Sensor resolution	2880 x 1620
Sensor Size	1/2.7"
Electronic shutter speed	1/25 ~ 1/100000s
Minimum lighting	0.005Lux
Ratio S / N	More than 65dB

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 12 mm
Maximum diaphragm opening	F/1.6
Angle of View	34° ~ 107°
Minimum focus distance	500mm

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5.5W
Amperage	460mA

DISTANCE DORI

Detect (Open lens)	69 m
Detect (Closed Lens)	192 m
Observe (Open lens)	28 m
Observe (Closed lens)	77 m
Recognize (Open lens)	14 m
Recognize (Closed lens)	38 m
Identify (Open lens)	7 m
Identify (Closed lens)	19 m

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Number of LEDs	2
IR ON/Off	Automatic / Manual
Smart IR	Yes
Starlight	Yes

AMBIENT

Operating temperature	-30 °C ~ 70 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	89 x 122 (Ø) mm
Material	Metal
Net weight	470 g
Weight with packaging	620 g

AXES

Motion	3-Axis
--------	---------------

GENERAL INFORMATION

Serie	LITE
Technology	HD-CVI
Type of camera	Minidome

