technical datasheet



P A R A D O X

Wireless curtain volumetric detector

NV37MR

DETECTION		
Detector type	Wireless	
Installation height	2 m	
Angle detection	5.7°	
Detection distance	10 m	
Coverage	Pets immunity mode: 7.5 x 2 m / Sharp Mode: 10 x 2 m	
Pets immunity	Up to 50 cm	
Antimasking	Detection up to 7.5 cm	
PIR detection advance at ground level (PIR Creep)	Sí	
Detection technology	Curtain volumetric	
MATERIAL AND DIMENSIONS		
MATERIAL AND DIMENSION	ONS	
MATERIAL AND DIMENSION Dimensions	ONS 123 x 61 x 43 mm	
Dimensions	123 x 61 x 43 mm	
Dimensions Net weight	123 x 61 x 43 mm 150 g 170 g	
Dimensions Net weight Weight with packaging	123 x 61 x 43 mm 150 g 170 g	
Dimensions Net weight Weight with packaging TECHNICAL SPECIFICATION	123 x 61 x 43 mm 150 g 170 g	
Dimensions Net weight Weight with packaging TECHNICAL SPECIFICATION LED indicators	123 x 61 x 43 mm 150 g 170 g DNS	
Dimensions Net weight Weight with packaging TECHNICAL SPECIFICATION LED indicators LED colors	123 x 61 x 43 mm 150 g 170 g DNS Yes Verde / Rojo	

Sensitivity adjustment Interruptores DIP

AMBIENT

Operating temperature	-40 °C ~ 70 °C
Degree of protection	IP54
Use	Indoor-outdoor
Maximum humidity	95%
CEDTIFICATION	

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	IV

POWER CONSUMPTION

Battery model	2 x AA
Battery duration	Up to 3 años

VIA RADIO

Frequency 868mHz

