



Minidome ip camera of 4 megapixels and optical zoom lens

IPC-HDBW2441R-ZAS

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	H.264: 32Kbps ~ 6144Kbps / H.265: 12Kbps ~ 6144Kbps
Compression	H.265 / H.264
Main stream	2688 × 1520 (1 fps-20 fps) / 2560 × 1440 (1 fps-25/30 fps)
Sub stream	704 × 576
Watermark	Yes
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	64 m
Detect (Closed Lens)	210 m
Observe (Open lens)	26 m
Observe (Closed lens)	84 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	42 m
Identify (Open lens)	6 m
Identify (Closed lens)	21 m

IMAGE

Sensor	CMOS ®
Sensor resolution	2688 x 1520
Sensor Size	1/2.9"

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	6 users
Web browser	Explorer / Chrome / Firefox
Management software	Smart PSS / DSS / DMSS
Mobile devices	Android / IOS (Apple)
IP address filter	Yes
Network disconnection	Yes
Cybersecurity	Yes, encrypted video

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes (4 areas)
Audio detection	Yes
Video Tamper	Yes
Classification Human / vehicle	Yes
SMD PLUS	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	7.7W
Amperage	670mA
PoE power	Yes
Type PoE	PoE 802.3af

NIGHT VISION

Night vision distance	40 m
Type of night vision	IR
Number of LEDs	2
IR ON/Off	Automatic / Manual
Starlight	Yes

technical datasheet

Electronic shutter speed	1/3 ~ 1/100000s
--------------------------	-----------------

Minimum lighting	Color: 0.008Lux / B/W: 0.0008Lux
------------------	----------------------------------

Ratio S / N	More than 56dB
-------------	----------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Anti vandal	IK10
-------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	95%
------------------	-----

LENS

Lens Type	Optical zoom
-----------	--------------

Focal distance	2.7 mm ~ 13.5 mm
----------------	------------------

Maximum diaphragm opening	F/1.5
---------------------------	-------

Angle of View	104° ~ 29°
---------------	------------

Minimum focus distance	800mm
------------------------	-------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Audio input	1 Input
-------------	---------

Audio compression	G.711A / G.711U / G.726 / PCM
-------------------	-------------------------------

Audio output	1
--------------	---

SYSTEM (CAMERAS)

Ram memory	128 MB
------------	--------

ROM memory	128 MB
------------	--------

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	--------------------

MATERIAL AND DIMENSIONS

Dimensions	94 x 122 (Ø) mm
------------	-----------------

Material	Metal
----------	-------

Net weight	520 g
------------	-------

Weight with packaging	680 g
-----------------------	-------

GENERAL INFORMATION

Serie	Serie 2X41
-------	------------

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	FTP / SFTP / Micro SD
-----------------	-----------------------

Storage anomaly	Yes
-----------------	-----

AXES

Motion	3-Axis
--------	--------

