



HIKVISION
accessories

2 wire 7" monitor

DS-KH6320Y-WTE2

POWER CONSUMPTION

Power mode	DC
Voltage	24V
Consumption (w)	4W
Amperage	800mA

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX
RAM	128 MB
ROM	32 MB

SCREEN

Type	TFT
Size	7"
Resolution	1024 x 600
Touch	Sí

AMBIENT

Operating temperature	-10 °C ~ 50 °C
Use	Indoor
Maximum humidity	90%

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Audio compression	G.711A / G.711U

GENERAL INFORMATION

Technology	2 Wire
------------	--------

CAPACITY

Events	400 (200 photos / 200 alarm records)
Warnings	200
Linked IP cameras	16
Linked phones	17

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / SIP / RSTP
IP connection	10 / 100Mbps autoadaptive
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n

INPUTS/OUTPUTS

Alarm input	8
RS485	1
Alarm output	2

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	200 x 140 x 23.6 mm

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Memory slot	SD up to 128Gb
-------------	----------------

