technical datasheet





Ip recorder of 8 channel and 12 mpx resolution with 8 PoE ports

NVR2108HS-8P-S3

D- [-	La aka Haki	/
PoE ports	8	Installation	Desk / Rack
Number of ports RJ45	1	Dimensions	260 x 232.7 x 47.6 mm
Velocità RJ45	10 / 100 Mbps	Material	Metal
Mobile	Android / IOS (Apple)	Net weight	890 g
devices		Weight with packaging	2000 g
ONVIF Remote Web	Yes Browser (ActiveX) / Smartphone	Chassis	10
vision	App / Smart PSS Software	POWER CONSUMPTION	
Type PoE	802.3af	Power mode	DC
PoE consumption	25.5W per port / 72W in total	Voltage	48V ~ 53V
Software	SmartPSS	Consumption (w)	10W
Арр	iDMSS/gDMSS	Amperage	1800mA
RECORDING		AMBIENT	
Maximum		Operating temperature	-10 °C ~ 55 °C
recording resolution	12 Mpx	Use	Indoor
Input bandwidth	80Mbps	Maximum humidity	93%
Video compression	H.265 / H.264	STORAGE	
Recording mode	Manual / Programmed / Motion Detection / Alarm	Number of supported har	rd drives 1
Audio compression	G.711A / G.711U / G.726 / PCM	Maximum hard disk size (Unit) 16 TB
Resolutions	12Mpx / 4K / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / D1	Type HDD	3,5 SATA"
Output bandwidth	60Mbps	VIDEO	
REPRODUCTION AND COPY OF SECURITY		IP Channels	8
Simultaneous	7 CO. 1 O. 32 CO. 11 1	Resolution IP cameras	12 Megapíxeles
cameras in reproduction	1/4/8/9	SYSTEM (RECORDERS)	
Play / Pause / Stop / Fast forward / Fast Playback backward / Rewind / Play by frame /		Processor	Industrial grade integrated processor
functions Full scr	een / Backup (cut/file) / Partially enlarge / Audio on/off	Operating system	Embedded LINUX
Backup mode	USB		
Synchronized playback	8		
VIDEO OUTPUT			
HDMI Output Numbe	r 1		
	uts 1		

technical datasheet

Similar video signals	HDMI and VGA	
SPECS AND FEATURES		
Serie	LITE	
Technology	IP	
AUDIO		
Audio Inputs	1	
Audio Outputs	1	
INPUTS/OUTPUTS		
USB 2.0	2	

