

**HIKVISION**  
HiWatch Series



## Ip recorder of 8 channel and 8 mpx resolution

**HWN-4108MH**

### NETWORK FEATURES

Number of ports RJ45	<b>1</b>
Speed RJ45	<b>10 / 100 Mbps</b>
Maximum number of users	<b>64</b>
Mobile devices	<b>Android / IOS (Apple)</b>
Remote vision	<b>Web Browser / Smartphone App and Hik-Connect Software.</b>
Software	<b>IVMS</b>
App	<b>Hik-Connect</b>

### RECORDING

Maximum recording resolution	<b>8 Mpx</b>
Input bandwidth	<b>80Mbps</b>
Video compression	<b>H.265+ / H.265 / H.264+ / H.264</b>
Audio compression	<b>G.711A / G.711U / G.722 / G.726</b>
Resolutions	<b>4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF</b>
Output bandwidth	<b>80Mbps</b>

### VIDEO OUTPUT

HDMI Output Number	<b>1</b>
Number of VGA outputs	<b>1</b>
Resolution HDMI	<b>4K</b>
VGA resolution	<b>1080P</b>
Similar video signals	<b>HDMI and VGA</b>

### AMBIENT

Operating temperature	<b>-10 °C ~ 55 °C</b>
Use	<b>Indoor</b>
Maximum humidity	<b>90%</b>

### INTELLIGENT VIDEO SYSTEM

VCA	<b>Si</b>
Classification Human / vehicle	<b>Yes</b>
Motion detection	<b>Yes, 2.0</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Desk / Rack</b>
Dimensions	<b>265 x 225 x 48 mm</b>
Material	<b>Metal</b>
Net weight	<b>1000 g</b>
Weight with packaging	<b>1260 g</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>10W</b>
Amperage	<b>1500mA</b>

### GENERAL INFORMATION

Serie	<b>HiWatch</b>
Technology	<b>IP</b>
Compatibility	<b>Hikvision HA series cameras</b>

### STORAGE

Number of supported hard drives	<b>1</b>
Maximum hard disk size (Unit)	<b>8 TB</b>
Type HDD	<b>3,5 SATA"</b>

### AUDIO

Audio Inputs	<b>1</b>
Audio Outputs	<b>1</b>

### VIDEO

IP Channels	<b>8</b>
-------------	----------

# technical datasheet

## INPUTS/OUTPUTS

USB 2.0 2

## REPRODUCTION AND COPY OF SECURITY

Smart search Yes

