## technical datasheet





**GENERAL INFORMATION** 

## 5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 4 channel and 1 mpx maximum resolution

### HWD-5104MH-G4

| RECORDING                                |   | NETWORK FEATURES              |   |
|--|---|-------------------------------|---|
| Maximum                                  |   | Number of ports               | 1   |
| recording resolution                     | 1 Mpx   | RJ45                          |   |
| Video                                    | 055. /11055 /11057. /11057  | Speed RJ45                    | 10 / 100 Mbps   |
| compression H.2                          | 265+ / H.265 / H.264+ / H.264                                     | Maximum<br>number of users    | 32  |
| Resolution<br>HDCVI recording            | 1 Megapixel (720P)  | Mobile devices                | Android / IOS (Apple)                                 |
| Resolution HDTVI recording               | 1 Megapixel (720p)  | Remote vision Web             | Browser / Smartphone App<br>and Hik-Connect Software. |
| Resolution recording AHD                 | 1 Megapixel (720p)  | Software                      | IVMS  |
| Images per 1080P Li                      | ite / 720P Lite / WD1 / 4CIF /<br>GA (1 ~15fps) / CIF (1 ~ 25fps) | App                           | Hik-Connect   |
| stream                                   |   | MATERIAL AND DIMENSI          |   |
| Images per second Extra 4CIF             | F (15fps) / CIF / QVGA (25fps)                                    | Installation                  | Desk / Rack   |
| stream                                   | (15165) / 611 / Q 7 67 (25165)                                    | Dimensions                    | 260 x 222 x 45 mm                                     |
| Video bit rate                           | 32 Kbps ~ 4 Mbps  | Material                      | Metal   |
| Audio compression                        | G.711U  | Net weight                    | 800 g   |
| Speed audio bits                         | 64Kbps per channel  | Weight with packaging         | 1300 g  |
| VIDEO                                    |   | POWER CONSUMPTION             |   |
| BNC channels                             | 4   | Power mode                    | DC  |
| IP Channels                              | 5, replacing the BNC  | Voltage                       | 12V   |
|  | channels  | Consumption (w)               | 16W   |
| Accepted IP cameras                      | 4 BNC cameras + 1 IP<br>camera                                    | Amperage                      | 1500mA  |
| Admitted resolutions<br>HDCVI            | 1080P / 720P  | AMBIENT                       |   |
| Admitted resolutions<br>HDTVI            | 1080P / 720P  | Operating temperature         | -10 °C ~ 55 °C  |
| Admitted resolutions                     | 1080P / 720P  | Use                           | Indoor  |
| AHD                                      |   | Maximum humidity              | 90%   |
| Cameras CVBS                             | Yes   | AUDIO                         |   |
| Resolution IP cameras                    | 2 Megapíxeles   | Audio Inputs                  | 1   |
|  |   | ·                             |   |
| VIDEO OUTPUT                             |   | A                             |   |
| VIDEO OUTPUT HDMI Output Number          | 1   | Audio Outputs                 | 1   |
|  | 1   | Audio Outputs  INPUTS/OUTPUTS | ı   |
| HDMI Output Number                       |   |                               | 2   |
| HDMI Output Number Number of VGA outputs | 1   | INPUTS/OUTPUTS                | 2   |

# technical datasheet

Serie HiWatch
Technology 5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)
Compatibility Hikvision HA series cameras

#### **STORAGE**

Number of supported hard drives 1

Maximum hard disk size (Unit) 4 TB

Type HDD 3,5 SATA"



### INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle

Motion detection

Yes, 2.0 on all analogue channels