technical datasheet





5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 8 channel and 1 mpx maximum resolution

HWD-5108MH-G4

RECORDING		NETWORK FEATUR	RES
Maximum recording	1 Mpx	Number of ports RJ45	1
resolution		Velocità RJ45	10 / 100 Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264	Maximum	64
Resolution HDCVI recording	1 Megapixel (720P)	number of users Mobile devices	Android / IOS (Apple)
Resolution HDTVI recording	1 Megapixel (720p)	Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Resolution recording AHD	1 Megapixel (720p)	Software	IVMS
Images per second Main stream	1080P Lite / 720P Lite / WD1 / 4CIF / VGA / CIF (1 ~15fps)	Арр	Hik-Connect
Images per second Extra stream	CIF / QVGA (1 ~ 15fps)	MATERIAL AND DIMENSIONS	
Video bit rate	32 Kbps ~ 4 Mbps	Installation	Desk / Rack
Audio compression	G.711U	Dimensions	260 x 222 x 45 mm
Speed audio bits	64Kbps per channel	Material	Metal
		Net weight	850 g
VIDEO	0	Weight with packag	ging 1340 g
BNC channels	8 10, replacing the BNC	POWER CONSUMP	TION
IP Channels	channels	Power mode DC	
Accepted IP cameras	8 BNC cameras + 2 IP camera	Voltage 12V	
Admitted resolutions	1080P / 720P	Consumption (w) 17W	
Admitted resolutions HDTVI	1080P / 720P	Amperage 1500mA	
Admitted resolutions	1080P / 720P	AMBIENT	
AHD Cameras CVBS		Operating temperature -10 °C ~ 55 °C	
	Yes	Use	Indoor
Resolution IP cameras	5 Megapíxeles	Maximum humidity	90%
VIDEO OUTPUT		AUDIO	
HDMI Output Number	1	Audio Inputs 1	
Number of VGA output	s 1	Audio Outputs 1	
Resolution HDMI	1080P		
Resolución VGA	1080P	REPRODUCTION AND COPY OF SECURITY	
Similar video signals	HDMI and VGA	Synchronized playback 8	
SPECS AND FEATURES		INPUTS/OUTPUTS	
Serie	HiWatch	USB 2.0 2	
-	D-CVI, HD-TVI, AHD, analog and		

technical datasheet

Compatibility Hikvision HA series cameras

STORAGE

Number of supported hard drives 1

Maximum hard disk size (Unit) 4 TB

Type HDD 3,5 SATA"

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle

Yes 20 on all analogue



