



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-T229HA

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux
Ratio S / N	Más de 52dB

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	106°
Minimum focus distance	1500mm

NIGHT VISION

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	88.4 x 112 (Ø) mm
Material	Metal and plastic
Net weight	340 g
Weight with packaging	570 g

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle classification)
Video Tamper	Yes
Classification	Yes
Human / vehicle	
Motion detection	Yes (human and vehicle)
2.0	

technical datasheet

Night vision distance	30 m
Type of night vision	Luz blanca
IR ON/Off	Automatic / Manual
Full Color	Yes

DISTANCE DORI

Detect	44 m
Observe	17 m
Recognize	8 m
Identify	4 m

AXES

Motion	3-Axis
--------	---------------

GENERAL INFORMATION

Serie	ColorVu
Technology	IP
Type of camera	Minidome

STORAGE

Storage Systems	FTP
-----------------	------------

