



AJAX

Wired volumetric detector

MOTIONCAM-FIBRA-B

TECHNICAL SPECIFICATIONS

Compatibility	Ajax Fibra panels
LED indicators	Yes
Tamper	Dual
Tiempo de intervalo para la conexión con el receptor	12 ~ 300 sec
Connection type	BUS
Protection against false alarms	Yes, algorithmic analysis
Transmission distance	Up to 2000 m

DETECTION

Detector type	Wired
Installation height	2.4 m
Angle detection	88.5° Horizontal / 80° Vertical
Detection distance	12 m
Detection speed	0,3 m/s ~ 2 m/s
Pets immunity	Up to 20 kg and 50 cm
Detection technology	Volumetric

POWER CONSUMPTION

Power mode	DC (via Hub Hybrid BUS)
Voltage	24V
Battery support	Included

SENSOR

Type of sensor	PIR
Sensitivity adjustment	Si
Digital temperature compensation	Yes

MATERIAL AND DIMENSIONS

Dimensions	135 x 70 x 66 mm
Material	Plastic
Net weight	140 g
Weight with packaging	190 g
Color	Black

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Degree of protection	IP50
Use	Indoor
Maximum humidity	75%

VERIFICACIÓN FOTOGRAFICA

Picture quality	640 × 480 / 320 × 240 (default) / 160 × 120
Reception time of a photo	Up to 9 sec
Series images	1 - 5 images

CERTIFICATION

Grade	2
Normative	EN50131

