

HIKVISION
accessories



9 ports cloud switch with 8 PoE ports

DS-3E1309P-EI

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

ETHERNET PORTS

POE ports	8
Uplink ports	1
POE Ports Speed	10 / 100
Uplink ports speed	10/100/1000
Number of Ethernet ports	9
Puertos PoE prioritarios	2 (priorizados en caso de congestión)

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

NET STANDARD

IEEE802,3af	Yes
IEEE802,3at	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	120W
Amperage	2500mA
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	110W

CHARACTERISTICS (SWITCH)

Data rate supported	3.6 Gbps
Packet redirection speed	2.6784 Mpps
Maximum transmission distance	300 m
Buffer Memory	4 Mb
PoE Watchdog	Yes

MATERIAL AND DIMENSIONS

Dimensions	170 x 93.1 x 27.6 mm
Material	Metal
Net weight	350 g
Weight with packaging	1090 g

SYSTEM (SWITCH)

MAC address table	16K
-------------------	-----

