

HIKVISION®



Ip recorder of 8 channel and 32
mpx resolution with 8 PoE ports

DS-7608NI-M2/8P

NETWORK FEATURES

PoE ports	8
Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Type PoE	802.3at / af
PoE consumption	120W
Software	IVMS
App	Hik-Connect

RECORDING

Maximum recording resolution	32 Mpx
Input bandwidth	128Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726 / AAC / MP2L2
Resolutions	32Mpx / 24Mpx / 12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	256Mbps

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W

MATERIAL AND DIMENSIONS

Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	3000 g

GENERAL INFORMATION

Serie	PRO
Technology	IP

INTELLIGENT VIDEO SYSTEM

POS	Yes
VCA	Si

REPRODUCTION AND COPY OF SECURITY

Synchronized playback	8
-----------------------	---

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	8K
Resolución VGA	1080P
Independent video signals	Yes

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	1
USB 3.0	1
Alarm output	1

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	16 TB
Type HDD	3,5 SATA"

AUDIO

Audio Inputs	1
Audio Outputs	1

VIDEO

IP Channels	8
-------------	---