

**MOVOK**  
ACCESSORIES



## Earth isolator with bnc connectors

**VK-ISOLATOR**

### TRANSMISSION

|                       |                      |
|-----------------------|----------------------|
| Impedancia de entrada | <b>75 Ohm</b>        |
| Impedancia de salida  | <b>75 Ohm</b>        |
| Anti-interferencias   | <b>&gt; 90dB</b>     |
| Ancho de banda        | <b>25MHz ~ 50MHz</b> |

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-20 °C ~ 60 °C</b> |
| Use                   | <b>Indoor</b>         |
| Lightning protection  | <b>2KV</b>            |

### PROTECTION

|                       |                          |
|-----------------------|--------------------------|
| Insulation voltage    | <b>AC 500V / DC 600V</b> |
| Insulation resistance | <b>&gt; 1M Ohm</b>       |

### GENERAL INFORMATION

|      |                                           |
|------|-------------------------------------------|
| Type | <b>Earth isolator with BNC connectors</b> |
|------|-------------------------------------------|

### MATERIAL AND DIMENSIONS

|                       |                          |
|-----------------------|--------------------------|
| Dimensions            | <b>42.8 x 28 x 20 mm</b> |
| Net weight            | <b>40 g</b>              |
| Weight with packaging | <b>60 h</b>              |

### PROPERTIES

|                   |                   |
|-------------------|-------------------|
| Input connection  | <b>BNC Macho</b>  |
| Output connection | <b>BNC Hembra</b> |

