



MOVOK

Minidome ip camera of 4 megapixels and fix lens

VK-IPC-T141-L-B

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	H.264 / H.265: 1792Kbps ~ 4Mbps
Compression	H.265 / H.264
Main stream	4Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	3W
Amperage	250mA
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Dimensions	97 x 110 (Ø) mm
Material	Carcasa: metal / Anillo: plástico
Net weight	350 g
Weight with packaging	470 g
Color	Black

DISTANCE DORI

Detect	58 m
--------	-------------

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/2.8'
Electronic shutter speed	1/25s ~ 1/1000s
Minimum lighting	0.01Lux
Ratio S / N	More than 56dB

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light	Sí
White light distance	20 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	102°

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Web browser	Explorer
Management software	MOVOK (CMS)

VIDEO ANALYSIS

Detection type	Advanced detection (human classification)
----------------	--

technical datasheet

Observe	23 m
Recognize	12 m
Identify	6 m

GENERAL INFORMATION

Serie	Serie 1
Technology	IP
Type of camera	Minidome

AXES

Motion	3-Axis
--------	--------

SMD

Yes

