



MOVOK

Minidome ip camera of 8 megapíxeles and optical zoom lens

VK-IPC-T381-ZAS-I

VIDEO (CAMERAS)

Video Resolution	8 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	4K (1 ~ 20fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	3840 x 2160
Sensor Size	1/2.8"
Electronic shutter speed	1/3 ~ 1/100000s

DISTANCE DORI

Detect (Open lens)	80 m
Detect (Closed Lens)	290 m
Observe (Open lens)	32 m
Observe (Closed lens)	115 m
Recognize (Open lens)	16
Recognize (Closed lens)	58 m
Identify (Open lens)	8 m
Identify (Closed lens)	29 m

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Classification Human / vehicle	Yes
SMD	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.2W
Amperage	520mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.6
Angle of View	109° ~ 30°

MATERIAL AND DIMENSIONS

Dimensions	110 x 122 (Ø) mm
------------	-------------------------

technical datasheet

Minimum lighting	Color: 0.007Lux / B/W: 0.0007Lux
------------------	---

Ratio S / N	More than 56dB
-------------	-----------------------

NIGHT VISION

Night vision distance	40 m
-----------------------	-------------

Type of night vision	IR
----------------------	-----------

IR ON/Off	Automatic / Manual
-----------	---------------------------

Starlight	Yes
-----------	------------

AMBIENT

Operating temperature	-40 °C ~ 60 °C
-----------------------	-----------------------

Degree of protection	IP67
----------------------	-------------

Use	Indoor-outdoor
-----	-----------------------

Maximum humidity	95%
------------------	------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	--------------------

Storage Systems	FTP / Micro SD
-----------------	-----------------------

Storage anomaly	Yes
-----------------	------------

SYSTEM (CAMERAS)

Ram memory	128 MB
------------	---------------

ROM memory	256 MB
------------	---------------

Material	Metal
----------	--------------

Net weight	630 g
------------	--------------

Weight with packaging	770 g
-----------------------	--------------

GENERAL INFORMATION

Serie	Serie 3
-------	----------------

Technology	IP
------------	-----------

Type of camera	Minidome
----------------	-----------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	------------

Audio compression	G.711A / G.711U / G.726 / G.726ASF
-------------------	---

AXES

Motion	3-Axis
--------	---------------

