

43



MOVOK

Bullet ip camera of 5 megapixels and optical zoom lens

VK-IPC-B351-ZAS-TI

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	67 m
Detect (Closed Lens)	239 m
Observe (Open lens)	27 m
Observe (Closed lens)	95 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	46 m
Identify (Open lens)	7 m
Identify (Closed lens)	23 m

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Heatmap	Yes
People counting	Yes
Classification Human / vehicle	Yes
SMD	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

NIGHT VISION

Night vision distance	50 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
Starlight	Yes
White light	Sí
White light distance	50 m

MATERIAL AND DIMENSIONS

Dimensions	244 x 77 x 76 mm
Material	Metal
Net weight	810 g

technical datasheet

Type PoE	PoE 802.3af	Weight with packaging	950 g
IMAGE		Color	White
Sensor	CMOS ®	LENS	
Sensor resolution	2880 x 1620	Lens Type	Optical zoom
Sensor Size	1/2.7"	Focal distance	2.7 mm ~ 13.5 mm
Electronic shutter speed	1/3 ~ 1/100000s	Maximum diaphragm opening	F/1.0
Minimum lighting	0.001Lux	Angle of View	99° ~ 28°
AMBIENT		AUDIO(CAMERAS)	
Operating temperature	-30 °C ~ 60 °C	Built in microphone	Yes
Degree of protection	IP67	Built in speaker	Yes
Use	Indoor-outdoor	Audio compression	G.711A / G.711U / G.726 / G.726ASF
Maximum humidity	95%	SYSTEM (CAMERAS)	
GENERAL INFORMATION		Ram memory	128 MB
Serie	Serie 3	ROM memory	256 MB
Technology	IP	TIOC	
Type of camera	Bullet	Siren	Yes
STORAGE		Light	White
MicroSD-Card	Up to 256Gb		
Storage Systems	FTP / Micro SD		
Storage anomaly	Yes		
AXES			
Motion	3-Axis		