

**HIKVISION**  
accessories



## 5 ports cloud switch with 4 PoE ports

**DS-3E1505P-EI**

### REMOTE MANAGEMENT

P2P	<b>Yes</b>
Software	<b>Hik Pro Connect / IVSM4200</b>
Reset switch	<b>Yes</b>
PoE port reset	<b>Yes</b>
Extended mode activation	<b>Yes, independently per port</b>
Port speed modification	<b>Yes</b>
Actual power consumption	<b>Yes, total and per port</b>
History of peak consumption	<b>Yes (up to 7 days)</b>
Real-time traffic information	<b>Yes, by port</b>
Connected device information	<b>Yes, for Hikvision equipment (IP, model, and SN)</b>
Automatic topology diagram	<b>Yes, for connected Hikvision devices</b>

### CHARACTERISTICS (SWITCH)

Data rate supported	<b>10 Gbps</b>
Packet redirection speed	<b>7.44 Mpps</b>
VLAN	<b>Yes (max 32 VLAN)</b>
DHCP	<b>Si</b>
Maximum transmission distance	<b>300 m</b>
Buffer Memory	<b>1 Mb</b>
Mirror port	<b>Si</b>
PoE Watchdog	<b>Yes</b>

### ETHERNET PORTS

POE ports	<b>4</b>
Uplink ports	<b>1</b>
POE Ports Speed	<b>10 / 100 / 1000</b>
Uplink ports speed	<b>10/100/1000</b>
Number of Ethernet ports	<b>5</b>

### NET STANDARD

IEEE802,3af	<b>Yes</b>
IEEE802,3at	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>54V</b>
Consumption (w)	<b>65W</b>
Amperage	<b>1200mA</b>
Standby consumption	<b>≤ 0.9W</b>
Maximum consumption per port (PoE)	<b>30W</b>
Total maximum consumption (PoE)	<b>60W</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Desk / wall</b>
Dimensions	<b>121.1 x 83.1 x 27.6 mm</b>
Material	<b>Metal</b>
Net weight	<b>220 g</b>
Weight with packaging	<b>750 g</b>

### AMBIENT

Operating temperature	<b>0 °C ~ 40 °C</b>
Use	<b>Indoor</b>
Maximum humidity	<b>95%</b>
Lightning protection	<b>6KV</b>

### SYSTEM (SWITCH)

MAC address table	<b>2K</b>
-------------------	-----------

