



Bullet hd-cvi camera of 2
megapixels and fix lens

HAC-HFW1200CM-IL-A

technical datasheet

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS
Day / night mode	Colour
Privacy mask	Up to 8 zones
Mirror	On / Off

NIGHT VISION

Night vision distance	20 m
Type of night vision	Dual light (IR+Luz blanca)
Number of LEDs	1
IR ON/Off	Automatic / Manual
Starlight	Yes
Full Color	Yes
White light	1
White light distance	20 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	2.6W
Amperage	220mA

MATERIAL AND DIMENSIONS

Dimensions	166.6 x 69.7 x 70 mm
Material	Metal
Net weight	320 g
Weight with packaging	430 g

AXES

Motion	3-Axis
--------	---------------

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Electronic shutter speed	1/25 ~ 1/100000s
Minimum lighting	Color: 0.01Lux / B/W: 0.001Lux
Ratio S / N	More than 65dB

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	102°
Minimum focus distance	500mm

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

GENERAL INFORMATION

Serie	LITE
Technology	HD-CVI
Type of camera	Bullet

DISTANCE DORI

Detect	41 m
Observe	17 m
Identify	4 m

AUDIO(CAMERAS)

Audio input	1 Input
-------------	----------------