



## HIKVISION®

### Minidome ip camera of 4 megapixels and optical zoom lens

#### DS-2CD1743G2-LIZSU

#### VIDEO (CAMERAS)

|                   |                                                    |
|-------------------|----------------------------------------------------|
| Video Resolution  | <b>4 Megapixels</b>                                |
| BLC               | <b>Yes</b>                                         |
| HLC               | <b>Yes</b>                                         |
| 3D-NR             | <b>Yes</b>                                         |
| AGC               | <b>Yes</b>                                         |
| AWB               | <b>Yes</b>                                         |
| WDR               | <b>WDR (120 dB)</b>                                |
| Images per second | <b>20fps</b>                                       |
| Video output      | <b>RJ45</b>                                        |
| Day / night mode  | <b>Automatic / Manual</b>                          |
| Privacy mask      | <b>Up to 4 zones</b>                               |
| Type of Codex     | <b>CBR / VBR</b>                                   |
| Bit rate          | <b>32Kbps ~ 8Mbps</b>                              |
| Compression       | <b>H.265+ / H.265 / H.264</b>                      |
| Main stream       | <b>4Mpx (1 ~ 20fps) / 1080P / 720P (1 ~ 25fps)</b> |
| Sub stream        | <b>720P / 640 x 480 / 640 x 360 (1 ~ 25fps)</b>    |
| Watermark         | <b>Yes</b>                                         |
| Mirror            | <b>On / Off</b>                                    |

#### NETWORK FEATURES

|                         |                                    |
|-------------------------|------------------------------------|
| IP connection           | <b>1 RJ45 (10M / 100M)</b>         |
| ONVIF                   | <b>Yes, type S , G and T</b>       |
| Maximum number of users | <b>Up to 32 users</b>              |
| Password protection     | <b>Yes</b>                         |
| Web browser             | <b>Explorer / Chrome / Firefox</b> |
| Management software     | <b>iVMS-4200 / Hik-Connect</b>     |
| Mobile devices          | <b>Android / IOS (Apple)</b>       |
| Live view               | <b>Up to 6 channels</b>            |

#### IMAGE

|                   |                    |
|-------------------|--------------------|
| Sensor            | <b>CMOS ®</b>      |
| Sensor resolution | <b>2560 x 1440</b> |
| Sensor Size       | <b>1/3"</b>        |

#### DISTANCE DORI

|                         |              |
|-------------------------|--------------|
| Detect (Open lens)      | <b>64 m</b>  |
| Detect (Closed Lens)    | <b>198 m</b> |
| Observe (Open lens)     | <b>25 m</b>  |
| Observe (Closed lens)   | <b>79 m</b>  |
| Recognize (Open lens)   | <b>13 m</b>  |
| Recognize (Closed lens) | <b>40 m</b>  |
| Identify (Open lens)    | <b>6 m</b>   |
| Identify (Closed lens)  | <b>20 m</b>  |

#### AUDIO(CAMERAS)

|                     |                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------|
| Built in microphone | <b>Yes</b>                                                                                                   |
| Audio input         | <b>1 Input</b>                                                                                               |
| Audio compression   | <b>G.711A / G.711U / G.722.1 / G.726 / AAC-LC / MP2L2 / PCM</b>                                              |
| Noise filter        | <b>SI</b>                                                                                                    |
| Sampling frequency  | <b>8kHz / 16kHz</b>                                                                                          |
| Bit rate            | <b>64 Kbps (G.711A / G.711U) / 16 Kbps (G.722.1 / G.726) / 16 ~ 64 Kbps (ACC-LC) / 32 ~ 160 Kbps (MP212)</b> |
| Audio output        | <b>1</b>                                                                                                     |

#### POWER CONSUMPTION

|                 |                    |
|-----------------|--------------------|
| Power mode      | <b>DC</b>          |
| Voltage         | <b>12V</b>         |
| Consumption (w) | <b>9.6W</b>        |
| Amperage        | <b>800mA</b>       |
| PoE power       | <b>Yes</b>         |
| Type PoE        | <b>PoE 802.3af</b> |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-30 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP67</b>           |
| Anti vandal           | <b>IK08</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>95%</b>            |

#### MATERIAL AND DIMENSIONS

# technical datasheet

|                          |                        |
|--------------------------|------------------------|
| Electronic shutter speed | <b>1/3 ~ 1/100000s</b> |
| Minimum lighting         | <b>0.005Lux</b>        |
| Ratio S / N              | <b>Más de 52dB</b>     |

## NIGHT VISION

|                       |                                                              |
|-----------------------|--------------------------------------------------------------|
| Night vision distance | <b>30 m</b>                                                  |
| Type of night vision  | <b>Dual light (IR+Luz blanca)</b>                            |
| Number of LEDs        | <b>3</b>                                                     |
| IR ON/Off             | <b>Automatic / Manual</b>                                    |
| Wavelength            | <b>850 nm</b>                                                |
| Smart Hybrid Light    | <b>Yes (switches from IR to colour with human detection)</b> |

## LENS

|                           |                       |
|---------------------------|-----------------------|
| Lens Type                 | <b>Optical zoom</b>   |
| Focal distance            | <b>2.8 mm ~ 12 mm</b> |
| Maximum diaphragm opening | <b>F/1.6</b>          |
| Angle of View             | <b>96.7° ~ 29.7°</b>  |
| Filtro IR                 | <b>Sí</b>             |

## GENERAL INFORMATION

|                |                 |
|----------------|-----------------|
| Serie          | <b>PRO</b>      |
| Technology     | <b>IP</b>       |
| Type of camera | <b>Minidome</b> |

## AXES

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

## INPUTS/OUTPUTS (CAMERAS)

|       |                           |
|-------|---------------------------|
| Alarm | <b>1 Input / 1 Output</b> |
|-------|---------------------------|

|                       |                            |
|-----------------------|----------------------------|
| Dimensions            | <b>97.6 x 121.5 (Ø) mm</b> |
| Material              | <b>Metal and plastic</b>   |
| Net weight            | <b>540 g</b>               |
| Weight with packaging | <b>740 g</b>               |

## VIDEO ANALYSIS

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| Detection type                 | <b>Advanced detection (person/vehicle classification)</b> |
| Motion detection               | <b>Yes</b>                                                |
| Video Tamper                   | <b>Yes</b>                                                |
| Classification Human / vehicle | <b>Yes</b>                                                |

## STORAGE

|                 |                             |
|-----------------|-----------------------------|
| MicroSD-Card    | <b>Hasta 512Gb</b>          |
| Storage Systems | <b>NAS / FTP / Micro SD</b> |

## SYSTEM (CAMERAS)

|              |            |
|--------------|------------|
| Reset button | <b>Yes</b> |
|--------------|------------|

