

MOVOK

Bullet ip camera of 8 megapixels and optical zoom lens

VK-IPC-B382-ZAS-TI



VIDEO (CAMERAS)

Video Resolution	8 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	4K (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	80 m
Detect (Closed Lens)	290 m
Observe (Open lens)	32 m
Observe (Closed lens)	115 m
Recognize (Open lens)	16
Recognize (Closed lens)	58 m
Identify (Open lens)	8 m
Identify (Closed lens)	29 m

IMAGE

Sensor	CMOS ®
Sensor resolution	3840 x 2160
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Motion detection	Yes (4 areas)
Heatmap	Yes
People counting	Yes
Classification Human / vehicle	Yes
SMD	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

NIGHT VISION

Night vision distance	50 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light	Sí
White light distance	50 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

MATERIAL AND DIMENSIONS

technical datasheet

Minimum lighting	Color: 0.007Lux / B/W: 0.0007Lux
------------------	---

Ratio S / N	More than 56dB
-------------	-----------------------

POWER CONSUMPTION

Power mode	DC
------------	-----------

Voltage	12V
---------	------------

Consumption (w)	6.2W
-----------------	-------------

Amperage	520mA
----------	--------------

PoE power	Yes
-----------	------------

Type PoE	PoE 802.3af
----------	--------------------

LENS

Lens Type	Optical zoom
-----------	---------------------

Focal distance	2.7 mm ~ 13.5 mm
----------------	-------------------------

Maximum diaphragm opening	F/1.6
---------------------------	--------------

Angle of View	109° ~ 30°
---------------	-------------------

GENERAL INFORMATION

Serie	Serie 3
-------	----------------

Technology	IP
------------	-----------

Type of camera	Bullet
----------------	---------------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	--------------------

Storage Systems	FTP / Micro SD
-----------------	-----------------------

Storage anomaly	Yes
-----------------	------------

Dimensions	244 x 77 x 76 mm
------------	-------------------------

Material	Metal
----------	--------------

Net weight	830 g
------------	--------------

Weight with packaging	1000 g
-----------------------	---------------

Color	White
-------	--------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	-----------------------

Degree of protection	IP67
----------------------	-------------

Use	Indoor-outdoor
-----	-----------------------

Maximum humidity	95%
------------------	------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	------------

Built in speaker	Yes
------------------	------------

Audio compression	G.711A / G.711U / G.726 / G.726ASF
-------------------	---

TIOC

Siren	Yes
-------	------------

Light	blue/ red Light
-------	------------------------

AXES

Motion	3-Axis
--------	---------------

