technical datasheet





Wireless panel HUB2-4G-DC6V-W

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2
LED indicators	Yes
POWER CONSUMPTION	
Power mode	DC
Voltage	4.2V ~ 16V
Built in battery	Not
Battery life	± 16 hours
Battery model	6V DC
Input current 2200mA @4.2V	/ DC / 500mA @16V DC

VIA RADIO

Output current

Frequency	868mHz
Transmission	Up to 2000 m (without obstacles)
distance	op to 2000 iii (manout obstacies)
Maximum	Class 4 (2W) / 850/900Mhz , Class 2
power RF	(1W) / 1800/1900MHz

ZONES

Maximum number of rooms	50
Maximum number of devices	100

SPECS AND FEATURES

Т	ype of Central	Wireless

SABOTAGE

Box tamper	Sí

COMMUNICATION

Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller
2G/3G	Yes
4G	Yes
Ethernet	Yes

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White

AMBIENT

1500mA

Operating temperature	5 °C ~ 40 °C
Use	Indoor

CERTIFICATION

Grade	2
Normative	EN50131

PARTITIONS AND MEMORIES

PROCCESSOR

Operating system OS Malevich

