



**HIKVISION**  
intrusion

## Transmitter via radio DS-PM1-I16O2-WE

### POWER CONSUMPTION

|                 |                       |
|-----------------|-----------------------|
| Power mode      | AC                    |
| Voltage         | 100V ~ 240V           |
| Consumption (w) | 30W                   |
| Battery support | Optional              |
| Battery model   | 12V 7Ah (no included) |
| Battery life    | Up to 36h             |
| Power output    | 2 x DC 12V 1A         |

### TECHNICAL SPECIFICATIONS

|                             |                                      |
|-----------------------------|--------------------------------------|
| LED indicators              | Yes                                  |
| LED colors                  | Verde / Rojo / Amarillo              |
| Tamper                      | Dual                                 |
| EOL resistors (end of line) | Sí                                   |
| Conexión a detector         | NC / NO / EOL (1k, 2.2k, 4.7k, 8.2k) |
| On-board inputs / outputs   | 16 / 2                               |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 40 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

### VIA RADIO

|                       |              |
|-----------------------|--------------|
| Frequency             | 868mHz       |
| Transmission distance | Up to 1100 m |

### GENERAL INFORMATION

|               |                       |
|---------------|-----------------------|
| Serie         | AXPRO                 |
| Technology    | Wireless              |
| Type          | Transmitter via radio |
| Compatibility | Hikvision panels      |

### MATERIAL AND DIMENSIONS

|                       |                     |
|-----------------------|---------------------|
| Dimensions            | 261 x 199 x 86.4 mm |
| Material              | Plastic             |
| Net weight            | 970 g               |
| Weight with packaging | 1440 g              |

### CERTIFICATION

|                     |    |
|---------------------|----|
| Grade               | 2  |
| Environmental class | II |

