



**HIKVISION**  
intrusion

## Electromagnetic relay

**DS-PM1-O1L-WE**

### POWER CONSUMPTION

|                       |                    |
|-----------------------|--------------------|
| Power mode            | <b>DC</b>          |
| Voltage               | <b>7V ~ 24V</b>    |
| Relay output type     | <b>NO / NC</b>     |
| Relay voltage output  | <b>DC 0V ~ 36V</b> |
| Relay Amperage output | <b>5A</b>          |

### MATERIAL AND DIMENSIONS

|                       |                        |
|-----------------------|------------------------|
| Dimensions            | <b>38 x 25 x 18 mm</b> |
| Material              | <b>Plastic</b>         |
| Net weight            | <b>25 g</b>            |
| Weight with packaging | <b>52 g</b>            |

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-10 °C ~ 55 °C</b> |
| Use                   | <b>Indoor</b>         |
| Maximum humidity      | <b>90%</b>            |

### TECHNICAL SPECIFICATIONS

|                |                            |
|----------------|----------------------------|
| Compatibility  | <b>Hikvision panels</b>    |
| LED indicators | <b>Yes</b>                 |
| LED colors     | <b>Azul / Verde / Rojo</b> |
| Tamper         | <b>Entrada para tamper</b> |

### TRANSMISSION

|           |                |
|-----------|----------------|
| Distance  | <b>1800 m</b>  |
| Frequency | <b>868 MHz</b> |

### GENERAL INFORMATION

|       |              |
|-------|--------------|
| Serie | <b>AXPRO</b> |
|-------|--------------|

