

**AJAX**

Seismic detector

SEISMOPROTECT-FIBRA-G3-W**DETECTION**

Detection distance	2 m radius (steel) / 4 m radius (concrete)
Temperature for alarm jump	70°
Vibration sensitivity	3 levels
Ignore first vibration	Sí, opcional
Detection technology	Seismic
Detección de inclinación	Yes, from 5° to 25°
Detección de choque	Yes

AMBIENT

Operating temperature	-25 °C ~ 70 °C
Degree of protection	IP43
Anti vandal	IK04
Use	Indoor
Maximum humidity	95%

POWER CONSUMPTION

Power mode	DC (via Hub Hybrid BUS)
Voltage	24V
Standby consumption	0.3mA
Maximum consumption	12mA

SENSOR

Type of sensor	Piezoeléctrico
Digital temperature compensation	Yes
Accelerometer	Yes

MATERIAL AND DIMENSIONS

Dimensions	88 x 88 x 20 mm
Material	Aluminum and polycarbonate
Net weight	380 g
Weight with packaging	660 g
Color	White

TECHNICAL SPECIFICATIONS

Tamper	Dual
Connection type	4 wires
Protection against false alarms	Yes, algorithmic analysis
Transmission distance	Up to 2000 m

GENERAL INFORMATION

Technology	Wired
Compatibility	Hub Hybrid (2G /4G)

CERTIFICATION

Grade	3
Normative	EN50131

