



## MOVOK

Minidome IP camera of 4 megapixels and fix lens

VK-IPC-T140-L-B

### VIDEO (CAMERAS)

Video Resolution	<b>4 Megapixels</b>
BLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>DWDR</b>
Images per second	<b>25fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Colour</b>
Privacy mask	<b>Up to 4 zones</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>H.264 / H.265: 1792Kbps ~ 4Mbps</b>
Compression	<b>H.265 / H.264</b>
Main stream	<b>4Mpx (1 ~ 25fps)</b>
Sub stream	<b>D1 (1 ~ 25fps)</b>
Mirror	<b>On / Off</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>3W</b>
Amperage	<b>250mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>120 x 125 (Ø) mm</b>
Material	<b>Metal and plastic</b>
Net weight	<b>260 g</b>
Weight with packaging	<b>360 g</b>
Color	<b>Black</b>

### AMBIENT

Operating temperature	<b>-20 °C ~ 60 °C</b>
Degree of protection	<b>IP67</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Sensor resolution	<b>2560 x 1440</b>
Sensor Size	<b>1/2.8'</b>
Electronic shutter speed	<b>1/25s ~ 1/1000s</b>
Minimum lighting	<b>0.01Lux</b>
Ratio S / N	<b>More than 56dB</b>

### NIGHT VISION

Night vision distance	<b>30 m</b>
Type of night vision	<b>Dual light (IR+Luz blanca)</b>
IR ON/Off	<b>Automatic / Manual</b>
White light	<b>Sí</b>
White light distance	<b>30 m</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, G type</b>
Web browser	<b>Explorer</b>
Management software	<b>MOVOK (CMS)</b>
Mobile devices	<b>Android / IOS (Apple)</b>

### LENS

Lens Type	<b>Fix</b>
Focal distance	<b>2.8 mm</b>
Maximum diaphragm opening	<b>F/2.0</b>
Angle of View	<b>102°</b>

### GENERAL INFORMATION

Serie	<b>Serie 1</b>
Technology	<b>IP</b>
Type of camera	<b>Minidome</b>

### VIDEO ANALYSIS

Detection type	<b>Basic motion detection (pixel difference)</b>
Motion detection	<b>Yes (4 areas)</b>

# technical datasheet

Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>
<b>DISTANCE DORI</b>	
Detect	<b>42 m</b>
Observe	<b>17 m</b>
Recognize	<b>9 m</b>
Identify	<b>4 m</b>
<b>AXES</b>	
Motion	<b>3-Axis</b>

