



HIKVISION
accessories

Ip of surface video intercom DS-KV6124-WBE1

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Mobile app	Hik-Connect
Bluetooth	Yes
Network protocol	TCP / IP
Memory slot	SD up to 128Gb
IP connection	10 / 100Mbps autoadaptive
Wi-Fi	6
Tipo de Wi-Fi	IEEE802.11 b / g / n / ax
ONVIF	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	1200mA
PoE power	Yes
Type PoE	PoE 802.3af

CAMERA

Resolution	4 Mpx
Horizontal viewing angle	150°
Diagonal angle of view	75°
Night vision	Yes, up to 3 m
Day / Night	IR
Video compression	H.264 / H.265 / MJPEG

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX
RAM	512 MB
ROM	4096 MB

GENERAL INFORMATION

Serie	PVPH
Technology	IP
Number of homes	1

CAPACITY

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	1
Exit button	1
Blocking entry	2
RJ45	1 x 10 / 100

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	164 x 69 x 24.7 mm
Material	Glass and plastic
Net weight	270 g
Weight with packaging	500 g

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Use	Outdoor
Maximum humidity	90%

IDENTIFICATION

Mode	Bluetooth / Keyboard / Card / Remote
Keyboard	Yes
Type of card	MIFARE 13.56MHZ
Maximum reading distance	2 cm ~ 2.5 cm

AUDIO (VIDEO INTERCOM)

Sound input	Omni-directional microphone
Sound output	Built-in speaker
Audio compression	G.711u / G.711a / G.726 / G.722.1 / G.729 / Opus / AAC-LD / AAC-LC

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Led indicator	Sí, 3

technical datasheet

Cards **10000**

Register **2000**

OPENING

Call elements **Simple button**

